

MITANOL MB 15

Low Viscosity HC-Synthetic Automatic Transmission Fluid

Properties

- Reduced viscosity for maximum fuel economy
- High load carrying capacity and extremely wear-reducing
- Superior friction value consistency
- No foam formation
- High thermal stability
- Soft switching operations even at medium temperatures
- Excellent viscosity-temperature behaviour
- Excellent oxidation stability
- Neutral towards common sealing materials

Application notes

- Especially for the latest Mercedes-Benz 7-speed automatic transmission 722.9 with code A89, 7-speed automatic transmission hybrid 724.2, transfer gear box type 205, 213, 217, 218, 222, 238, 253, 257, 290 with transmission 725.0 and transfer gear box type 257 with transmission 725.1
- **MITANOL MB 15 cannot** be used in older Mercedes-Benz automatic transmissions and is **not** backwardly compatible

Observe manufacturer's instructions!

Service description

Recommendation*:

- MB 236.15

TYPICAL PARAMETERS	METHODS	UNITS	MITANOL MB 15
Density at 15°C	ASTM D4052	kg/m ³	847
Viscosity at 40°C	ASTM D445	mm ² /s	20.9
Viscosity at 100°C	ASTM D445	mm ² /s	4.81
Viscosity index (VI)	ASTM D2270	-	158
Pour point	ASTM D6892	°C	-42
Flash point COC	ASTM D92	°C	178
Colour	-	-	blue

* meets the requirements of the OEM manufacturer.
 The stated values may vary within the usual commercial range.