

MITANOL X-Force 0W-30 Special V

HC-synthetic high-performance low viscosity engine oil for Volvo passenger cars

Properties

MITANOL X-Force 0W-30 Special V is a synthetic high-performance low viscosity engine oil. The lowered HTHS viscosity enables fuel savings in the cold start phase and in short-distance traffic.

Guarantees highest engine cleanliness and best wear protection. The product is suitable for use in Volvo passenger cars with the latest efficiency-enhanced Euro 4, 5, 6 engine concepts with or without turbocharger, direct injection, multi-valve or hybrid technology.

MITANOL X-Force 0W-30 Special V guarantees a fuel-saving potential and contributes to the protection of the environment by reducing CO₂ emissions.

Application notes

MITANOL X-Force 0W-30 Special V with the approval VOLVO VCC 95200377 is mandatory for gasoline and diesel engines of the B5, B6, B8, D5 series as well as hybrid drives D8.PHEV as of 2005.

Service description

Specifications:

- ACEA A5/B5
- API SL

Recommendations*:

- Volvo VCC 95200377

TYPICAL PARAMETERS	METHODS	UNITS	MITANOL X-Force 0W-30 Special V
Density at 15°C	DIN 51 757	kg/m ³	845
Viscosity 40°C	DIN 51 562	mm ² /s	52.5
Viscosity 100°C	DIN 51 562	mm ² /s	9.89
Viscosity index (VI)	DIN ISO 2909	-	178
Viscosity at -35°C	DIN 51 377	mPa.s	5930
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	224

October 2020

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.